Keypads / iSCPBerlin

iSCP Berlin

IS-TP-CP-BERLIN

Specifications

- Controlpad with triple-spaced LCD display
- Free menu configuation - up to 150 entries
- 5 navigation keys (Home, Back, Selection and Up/Down)
- 4 softkeys with LED
- Individual surface design as inlay
- Up to 16 units at one RS-485 bus pin
- Gateway: RS-485, RS-232
- Operating Voltage: 12V / 100mA
- Cover (160 x 90)mm
- Installation in standard joint box (e.g. Kaiser Art. Nr. 9062-02)

Keypads

Das iSCPBerlin besticht durch seine schlichte Form und sein zeitgemäßes Design. Das dreizeilige Display verdunkelt sich nach einstellbarer Zeit. Die silbernen Tasten und der weiße Rahmen in der spiegelnden Plexiglas Oberfläche lassen sich mit einem individuellen Inlay ergänzen. Hierbei handelt es sich um einen einfachen Papiereinschub bei dessen Design keine Grenzen gesetzt sind.

Die Menüstruktur im Display lässt sich per PC Software frei konfigurieren. So lässt sich eine Menüstruktur mit „Unterseiten " erstellen sowie festlegen, um was für Eingaben es sich handelt. Es können beispielsweise einfache Wahlfunktionen (Ein/Aus) angelegt werden, wie auch „stufenlose" Werte um Licht zu dimmen oder Lautstärken zu wählen.
Fünf Buttons (Home, Zurück, Auswahl und Hoch/Runter) dienen zur Menüauswahl. Die vier Taster sind frei verwendbar, bzw. von der Mediensteuerung auswertbar ebenso wie die entsprechenden LEDs auf den Tasten.
Über einen RS-485 Bus können bis zu 16 Geräte kaskadiert werden, oder ein Gerät an einer RS-232 Schnittstelle betrieben werden.

Keypads

The iSCPBerlin captivates with its simple appearance and contemporary design.
The three-line display dims to dark after an adjustable time of none use. Covered by a reflective Plexiglas surface the silver keys and the white frame can be complemented by a individual inlay. Being a common paper inlay it can come in many designs.

The menu structure of the display can be configured via PC software. That way the user can create a nested menu structure and define different item functionality. For example, simple toggle functionality (on/off) or sliding values to dim light or to adjust sound volume.

The display navigation is handled by five buttons (Home, Back, Select and Up/Down). In addition there are four key buttons and correspondent LEDs that can be indicated by the media control system for any purpose.
Up to 16 iSCPBerlin units can be cascaded via a RS-485 bus, or one unit can be operated at one RS-232 connection.

inSynergie GmbH
Maarweg 56
53619 Rheinbreitbach

phone: +49 (0) 2224 98933-0
fax: +49 (0) 2224 98933-22

www.inSynergie.eu
info@inSynergie.com
info@inSynergie.de